HD DVR WH-410

H.264 Compression

4CH HD-SDI Input (720p or 1080p)

HDMI & Output Full HD (Max 1920x1080p)

4CH Audio In & 1CH Audio Out

Multi Channel Display and Digital Zoom Monitoring

Support Mobile Device

2 HDD (up to 6TB)

***SPESIFICATION**

MODEL			WH-410	WH-710
Video	Camera Input(NTSC,PAL)		HD-SDI 4ch	HD-SDI 7ch
	Output		1HDMI, 1VGA	
Audio	Audio Input		4 RCA	
	Output		1 RCA	
Display	Split Display		1/4	1/4/7
	HDMI Resolution		1080p or 1080i	
	VGA Resolution		From 1024*768 up to 1920*1080	
Recording	Compression(Video / Audio)		H.264 / ADPCM	
	Resolution(Pixel)		1080P(1920*1080), 720P(1280*720)	
	Mode		Normal, Event(Alarm, Motion), Schedule	
	Max Recording Frame		120fps@1080P	210fps@1080P
Playback	Split Display		1, 4	1, 4, 7
	Max Playback Frame		30fps@1080P	
	Search Mode		Date & Time, Calendar, Event(Alarm, Motion, Audio), Bookmark	
	Mode		Play, REW & FF, Slow, Frame to Frame, Pause, Replay	
Network	Network Interface		10/ 100/ 1000 Mbps Ethernet(RJ-45)	
	Protocol		TCP/IP, SMTP, HTTP, DHCP, PPPOE(ADSL), RTP/ RTSP	
	Serial Communicaton		RS-485 Serial Port X2 (PTZ & Keyboard control)	
	Application(PC Client)		Windows2000 / XP / Windows Vista	
	Web Browser		Internet Explorer 5.0 Higher(DVRs Contorl or Viewing)	
	Event Transport		E-mail notification when Event Occurs	
	Viewing / User Access		Remote Client, CMS, Mobile Viewer / Up to 25 users	
Storage & Backup	Storage Device		2 internal HDDs (up to 6TB)	
	Backup Interface		USB 2.0x2ea, Via Network	
	Backup Device		External HDD, Memory Stick	
	Backup File Fomat		EXE, AVI(Video Clip)	
Alarm	Sensor input		4(TTL)	
	Relay output		1 Relay	
Control	Event Log		Up to the 5000 events (Alarm, Motion, Video&Power Loss,Power&Record On/Off)	
	Controller		IR Remote Control/Mouse	
	Pan/Tilt Camera		Control From RS485 Interface/ Via Network	
Others	PTZ Protocol		12models including Pelco-P, Pelco-D, Vista-PD,Samsung and LG	
	Operating System		Embeded Linux	
	Power Source		DC 12V/ 3.5A	
	Power Consumption		40W	
	Weight	Unit/ Box	3.0Kg / 4.0Kg	
	Dimension	Unit/ Box	350(W)*250(D)*72(H)mm / 400(W)*340(D)*150(H)mm	